

Hisense

Lista sa podacima aparata

Unutrašnja jedinica - model	KE70BT2EG
Spoljašnja jedinica - model	KE70BT2EW
Snaga zvuka pri standardnim uslovima merenja (unutrašnji / spoljašnji) [db(A)]	64 / 65
Sredstvo za hlađenje	R32
GWP	675
Dodatni iznos	1320
CO2 ekvivalent (tona)	0,891
SEER	6,2
Energetski razred - hlađenje	A++
Godišnja potrošnja prilikom hlađenja [kWh/leto][1]	367
Nominalno opterećenje hlađenja (Pdesign)[KW]	6,5
SCOP (Sezonski koeficient učinkovitosti - ogrevanje)	4,0
Energetski razred - grejanje (prosečna sezona)	A+
Godišnja potrošanja prilikom grejanja (prosečna sezona)[kWh/leto][2]	1908
Topla sezona grejanja [kW]	6,3
Hladna sezona grejanja [kW]	-
Nominalno opterećenje grejanja (Pdesign)[KW]	6,5
Declared capacity at reference design condition (heating average season)[KW]	5,45
Back up heating capacity at reference design condition (heating average season) [KW]	-

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere.

This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Sadrži fluorirane gasove staklene bašte

Importer: Partizanska 12, 3320 Velenje, Slovenija info@gorenje.si / +386 3 899 1000

Proizvođač: Partizanska 12, 3320 Velenje, Slovenija info@gorenje.si / +386 3 899 1000

[1][2] Godišnja potrošnja energije "XYZ" [kWh] temelji se na standardnim rezultatima ispitivanja. Stvarna potrošnja energije zavisi od upotrebe i lokacije instalacije

Upozorenje: molim proverite informacije na nalepnici modela na tipskoj pločici